



Mod. 330 M 60°

Mod. 370 M 60°

Mod. 420 M 60°




MANUAL 60° RIGHT









Mod. 330 M 60°

Mod. 370 M 60°

Mod. 420 M 60°

Model		330 M 60°		
		90°	45°	60°
Cutting Capacity mm		250	200	125
		220	180	125
		320x140	200x90	130x125
Band dimensions		LxWxH mm 3010x27x0.9		

Model		370 M 60°		
		90°	45°	60°
Cutting Capacity mm		280	230	150
		240	210	150
		370x150	250x120	140x130
Band dimensions		LxWxH mm 3120x27x0.9		

Model		420 M 60°		
		90°	45°	60°
Cutting Capacity mm		280	240	165
		235	230	170
		420x160	250x180	170x170
Band dimensions		LxWxH mm 3270x27x0.9		

TECHNICAL DATA

Cutting Speed	Standard	m/1' 35-70
	Optional	m/1' 20÷100 (with variator)
Working surface height		mm 835
Blade motor	Standard	kW 0.7-1.4
	Optional	kW 1.1
Coolant electrical pump		kW 0.1
Dimensions		LxWxH mm 1700x1400x1900
Transport dimension		LxWxH mm 1600x800x1500
Weight		Kg 430

BIANCO

BIANCO srl
 I - 24060 Carobbio degli Angeli (BG) Italy - Via Kennedy, 8
 Tel. +39 035.42.52.511 - Fax + 39 035.42.52.542
 Sito internet: www.bianco.bg.it - E mail: info@bianco.bg.it

MOD. 330 - 370 - 420 M 60°

Manual 60° Right

The 330 - 370 - 420 M 60° are completely manual machines. Robust and particularly recommended for cutting medium-size round, flat pieces and structural materials. Ideal for small and medium-size businesses in the structural metal sector, this machine can also be used for cutting at angles of up to 60 degrees. The care taken with the machine's design and the technical features means high precision cutting and absolute reliability.

TECHNICAL SPECIFICATIONS

Base with welded, standardised structure • Bow made out of hardened aluminium and mounted onto conical roller ball bearings • Vice unit made from spheroid cast iron • Reducer unit consists of hardened and ground gears • Adjustable width blade-guide slide blocks • Low voltage electrical system in line with CE norms • Embossed enamel Finish: RAL 3001 red bow - RAL 7036 grey base







STANDARD ACCESSORIES

0-500 mm arm with checking • Pieces discharge slide

ACCESSORIES AVAILABLE ON REQUEST

Material infeed/outfeed roller track available in various sizes with graduated rule and mechanical length stop • Pneumatic vice • Hydraulic brake with electric skip • Mechanical blade speed variator 20/100 mt/1' • Gravity down-feed over Hydraulic brake and flow regulator

RECOMMENDED TOOTHING IN RELATION TO MATERIAL SECTION

Material	Thickness	Z/1" INCH	Dimensions	Z/1" INCH	
				Dimensions	Z/1" INCH
	2÷6	6/10-5/8		<50	5/8
	4÷10	4/6		50÷100	4/6
	>10	3/4		>100	3/4

RECOMMENDED BANDS: BIMETAL KOBALT M42

Pneumatic vice



Blade speed variator



Gravity down-feed